

# NF 5 DIAPHRAGM LIQUID PUMP



NF 5 KP.51DC-M



NF 5 KPDCB-4

## ADVANTAGES

- Small and powerful
- Self priming and excellent for pressure
- Extreme chemical resistance
- Dry running, durable and maintenance free




PERFORMANCE DATA					
Basic types	NF 5 DC-M		NF 5 DCB	NF 5 DCB-4	
Material options	КР	КТ	тт		
Pump head	PP	PP	PVDF		
Diaphragm	EPDM	PTFE	PTFE		
Valves	EPDM	FFKM	FFKM		
Flow rate (ml/min) at atm. pressure	≥70			≥40	≥5 - 40
Suction height (mWg)	3	2.5			
Pressure head (mWg)	10				
Permissible ambient temperature (°C)	+5 to +4	0			
Permissible liquid temperature (°C)	+5 to +8	0			
Weight (g)	56			48	
IP protection factor	30			40	
ELECTRICAL DATA					
Operation voltage (V)	12 / 24			12 / 24	12 - 26
Power consumption (W)	1.44			1.0 / 1.2	1.1
l load max. (A)	0.12/0.0	6		0.08 / 0.05	0.09 - 0.04

## POSSIBLE AREAS OF USE


- Analysers
- Laboratory
- Cleaning industry
- Printing

# NF 5 DC-M

PERFORMANCE DATA			
Series model	Flow rate at atm. pressure (ml/min)	Max. suction height (mWg)	Max. pressure head (mWg)
NF 5 KP DC-M	≥ 70	3	10
NF 5 KT/TT DC-M	≥ 70	2.5	10



#### NF 5 DC-M FLOW CURVE




# NF 5 DCB

PERFORMANCE DATA			
Series model	Flow rate at atm. pressure (ml/min)	Max. suction height (mWg)	Max. pressure head (mWg)
NF 5 KP DCB	≥ 70	3	10
NF 5 KT/TT DCB	≥ 70	2.5	10


# NF 5 DCB-4


PERFORMANCE DATA			
Series model	Flow rate at atm. pressure (ml/min)	Max. suction height (mWg)	Max. pressure head (mWg)
NF 5 KP DCB-4	≥ 5-40	3	10
NF 5 KT/TT DCB-4	≥ 5-40	2.5	10




Dimensions in mm

#### **NF 5 DCB FLOW CURVE**






#### NF 5 DCB-4 FLOW CURVE



#### NF 5 DCB-4 CONTROL CURVE



OPTIONS		
Name	Picture	Details
Motors	A.	Various voltage options, higher and lower service life
Electrical connections		Molex, AMP etc.
Hydraulic connections		Internal thread, manifold connection etc.
Head material		PPS (polyphenylene sulfide) for special require- ments regarding chemical resistance.



#### **NSF National Sanitary Foundation**

This certification will confirm that all of the pumps with the code .51 are certified for the use with foods/consumables.



#### DIGITAL CUSTOMIZATION

Thanks to digital technology, this pump can be quickly adapted to the customer's system. This is done by parametrizing the firmware of the motor at KNF.

ACCESSORIES				
Description	Illustration	Details		
Diaphragm pressure control valve		The pressure control valve can be used for a more accurate control of flow against a fluctuat- ing back pressure, metering into a vacuum and from a pressurised system.		
Pulsation damper		This very versatile pulsation damper reduces the vibration in hoses and pipes and it helps to remove pulsation which is preventing the system from functioning correctly.		
Filter	×-•	KNF filters protect both pumps and other upstream instrumentation and hydraulic circuits against particulate, crystals and fibres which can improve optimum operation.		
Tubing		Various diameters and materials		

The performance values for the series models shown on this data sheet were determined under test conditions. The actual performance values may differ and depend in particular on the usage conditions and therefore on the specific application, on the parameters of the components involved in the user's system and on any technical modifications carried out which deviate from the standard configuration or the as delivered condition. If individual designs have been created for specific customers on the basis of series models, other technical performance data may apply.

Before operation begins, the relevant operating instructions and/or assembly or installation instructions should be read and the safety information contained in these instructions should be noted.

KNF reserves the right to make changes to the product and the associated documentation without prior notice to the customer.



www.knf.com

# YOUR LOCAL PARTNER AROUND THE WORLD

### KNF SALES ORGANIZATION

Australia KNF Regional Office Moreland West VIC 3055 Tel. +61 3 9386 4959 info@knf.com.au www.knf.com.au

Benelux Netherlands KNF Verder B.V. 3451 GG Vleuten Tel. +31 30 677 92 40 info@knf-verder.nl www.knf-verder.nl

Benelux Belgium and Luxemburg KNF Verder N.V. 2630 Aartselaar Tel. +32 3 871 96 24 info@knf.be www.knf.be

China KNF Technology (Shanghai) Co., Ltd. Shanghai 201203 Tel. +86 21 5109 9695 info@knf.com.cn www.knf.com.cn

France KNF Neuberger SAS 68128 Village-Neuf Tel. +33 389 70 35 00 info@knf.fr www.knf.fr

Germany KNF Neuberger GmbH 79112 Freiburg Tel. +49 7664 5909 0 info@knf.de www.knf.de India KNF Pumps + Systems (India) Pvt. Ltd. Hinjewadi Pune 411 057 Tel. +91 20 640 13 923 info@knfpumps.in www.knfpumps.in

Italy KNF Italia S.r.l. 20063 Cernusco s. Naviglio (MI) Tel. +39 02 929 04 91 info@knf.it www.knf.it

Japan KNF Japan Co. Ltd. Tokyo 104-0033 Tel. +81 3 3551 7931 info@knf.co.jp www.knf.co.jp

Korea KNF Neuberger Ltd. 135-502 Seoul Tel. +82 2 959 0255 knf@knfkorea.com www.knfkorea.com

Latin America KNF Regional Office Tel. +1 609 649 1010 gb@knf.com www.knf.com/es

Morocco, Tunisia, Algeria KNF Neuberger SAS 68128 Village-Neuf Tel. +33 389 70 35 00 info@knf.fr www.knf.fr Singapore KNF Regional Office Tel. +65 9722 1994 info@knf.com.sg www.knf.com.sg

Sweden, Finland, Denmark, Norway KNF Neuberger AB 117 43 Stockholm Tel. +46 8 744 51 13 info@knf.se www.knf.se

Switzerland KNF Neuberger AG 8362 Balterswil Tel. +41 71 973 99 30 knf@knf.ch www.knf.ch

UK, Ireland KNF Neuberger U.K., Ltd. Witney, Oxfordshire OX28 4FA Tel. +44 1993 77 83 73 info@knf.co.uk www.knf.co.uk

USA, Canada KNF Neuberger, Inc. Trenton, NJ 08691-1810 Tel. +1 609 890 8600 knfusa@knf.com www.knfusa.com

## KNF PRODUCT CENTERS

Gas Pumps KNF Neuberger GmbH DE-79112 Freiburg info@knf.de www.knf.de Micro Gas Pumps KNF Micro AG CH-6260 Reiden info@knf-micro.ch www.knf-micro.ch Liquid Pumps KNF Flodos AG CH-6210 Sursee info@knf-flodos.ch www.knf-flodos.ch